



KEY FEATURES


- A high performance, top hung sliding door with recessed top and bottom rails and jamb stiles.
- The custom Centor E3 quad rollers are fully adjustable up and down when the door is in the frame.
- The extra strong multi hollow meeting stiles allow large sliding doors to be fabricated in high wind load areas, refer panel strength tables.
- There are a large variety of door combinations (XF, FX, FXXF, XXF, FXX, FXXXXF, XXXF, FXXX, FXXXXXXF and corner doors).
- We can fit Centor SIE roller screens behind Series 704 sliding doors up to 7400mm wide.
- Square clean lines with soft radius edges on internal meeting stile corners.
- Doors fitted with custom mortice lock at meeting stiles. Lock only accessible from the inside. Slimline stiles possess built-in finger grip inside and out.




The door head is fully concealed into the building envelope to ensure clear glass sight lines right to the ceiling.



Large sliding panels are supported at the head with heavy duty rollers for smooth operation.



When recessed into the floor, clear glass sight lines can be achieved and the sill can be combined with a FlowTHRU™ drain for the ultimate flush sill transition.



The stiles and jamb are fully recessed into the building envelope to create clear sight lines around the entire door to maximise views and deliver excellent energy efficiency.

GENERAL

Max Panel Height*
3300mm

Max Panel Width*
2500mm

Max Glass Thickness
28mm

Frame Depth
Various

ENERGY

UW Range
2.2-4.2

SHGC Range
0.15-0.59

WEATHER

Maximum Water
300Pa

ACOUSTICS

